

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

913 Brake Paste MP91300200AB

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant

**1.3. Details of the supplier of the safety data sheet**

Company name:	TUNAP GmbH & Co. KG	
Street:	Buergermeister-Seidl-Strasse 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600-0	Telefax: +49 (0) 8171/1600-40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

**1.4. Emergency telephone number:** 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 3; H229

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Signal word:** Warning**Hazard statements**

H229 Pressurised container: May burst if heated.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P251 Do not pierce or burn, even after use.

**Special labelling of certain mixtures**

EUH208 Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts, Sulfonic acids, petroleum, calcium salts, Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts.  
May produce an allergic reaction.  
< 1 % by mass of the contents are flammable.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 2 of 13

**Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts			3 - < 5 %
	271-529-4		01-2119492627-25	
	Skin Sens. 1B; H317			
13463-67-7	titanium dioxide			1 - < 3 %
	236-675-5	022-006-00-2		
	Carc. 2; H351			
61789-86-4	Sulfonic acids, petroleum, calcium salts			1 - < 3 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			1 - < 3 %
	274-263-7		01-2119492616-28	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
68584-23-6	271-529-4	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	3 - < 5 %	
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100			
13463-67-7	236-675-5	titanium dioxide	1 - < 3 %	
	inhalation: LC50 = > 6,8 mg/l (dusts or mists); dermal: LD50 = > 10000 mg/kg; oral: LD50 = > 10000 mg/kg			
61789-86-4	263-093-9	Sulfonic acids, petroleum, calcium salts	1 - < 3 %	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100			
70024-69-0	274-263-7	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	1 - < 3 %	
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = > 4000 mg/kg; oral: LD50 = > 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100			

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.



## Safety Data Sheet

according to UK REACH Regulation

### 913 Brake Paste MP91300200AB

Revision date: 22.03.2021

Product code: 1103533

Page 3 of 13

#### After ingestion

Rinse mouth immediately and drink plenty of water.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Danger of bursting container.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### **6.3. Methods and material for containment and cleaning up**

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 4 of 13

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Advice on protection against fire and explosion**

Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Further information on handling**

Avoid contact with skin and eyes.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 5 of 13

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
61789-86-4	Sulfonic acids, petroleum, calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm <sup>2</sup>
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm <sup>2</sup>
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 6 of 13

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
61789-86-4	Sulfonic acids, petroleum, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)  
Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.  
Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min  
Thickness of the glove material 0,45 mm  
EN ISO 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 7 of 13

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: A  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

**Environmental exposure controls**

Observe legal regulations and provisions.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Aerosol  
Colour: blue  
Odour: characteristic

**Test method****Changes in the physical state**

Melting point/freezing point: not determined  
Boiling point or initial boiling point and boiling range: 200 °C

**Flammability**

Solid/liquid: not determined  
Gas: not applicable  
Lower explosion limits: not applicable  
Upper explosion limits: not applicable  
Auto-ignition temperature: 250 °C

**Self-ignition temperature**

Solid: not determined  
Gas: not applicable

Decomposition temperature: not determined

pH-Value (at 20 °C): not applicable DIN 19268

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

**Solubility in other solvents**

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: not determined

Density: 1,2 g/cm<sup>3</sup> DIN 51757

Relative vapour density: not determined

**9.2. Other information****Information with regard to physical hazard classes**

Oxidizing properties  
Not oxidising.

**Other safety characteristics**

Solid content: not determined

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 8 of 13

Evaporation rate: not determined

**Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

**10.4. Conditions to avoid**

Protect from frost.

**10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

**10.6. Hazardous decomposition products**Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.



**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
13463-67-7	titanium dioxide				
	oral	LD50 > 10000 mg/kg	Rat		
	dermal	LD50 > 10000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 > 6,8 mg/l	Rat		
61789-86-4	Sulfonic acids, petroleum, calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts, Sulfonic acids, petroleum, calcium salts, Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.



## Safety Data Sheet

according to UK REACH Regulation

### 913 Brake Paste MP91300200AB

Revision date: 22.03.2021

Product code: 1103533

Page 10 of 13

#### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### SECTION 12: Ecological information

#### 12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts					
	Acute fish toxicity	LC50 >10000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
13463-67-7	titanium dioxide					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 61 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 > 10 mg/l	48 h	Daphnia pulex		
	Fish toxicity	NOEC > 1000 mg/l	2 d	Leuciscus idus (golden orfe)		
	Algae toxicity	NOEC 1 mg/l	3 d	Pseudokirchneriella subcapitata		
	Crustacea toxicity	NOEC > 3 mg/l	30 d	Daphnia magna		
61789-86-4	Sulfonic acids, petroleum, calcium salts					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1993)	EPA OTS 797.1300
	Acute bacteria toxicity	(EC50 > 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)	OECD Guideline 209
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts					
	Acute fish toxicity	LC50 >10000 mg/l	96 h	Cyprinus carpio (Common Carp)		
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Acute bacteria toxicity	(EC50 > 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209

#### 12.2. Persistence and degradability



## Safety Data Sheet

according to UK REACH Regulation

### 913 Brake Paste MP91300200AB

Revision date: 22.03.2021

Product code: 1103533

Page 11 of 13

The product has not been tested.

#### **12.3. Bioaccumulative potential**

The product has not been tested.

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
61789-86-4	Sulfonic acids, petroleum, calcium salts	> 4,46
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	18,05

#### **12.4. Mobility in soil**

The product has not been tested.

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

No information available.

#### **Further information**

Avoid release to the environment.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### **List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

##### **Contaminated packaging**

Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.2
Classification code:	5A

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 12 of 13

Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 3  
Tunnel restriction code: E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.2  
Classification code: 5A  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2, see SP63  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, non-flammable  
**14.3. Transport hazard class(es):** 2.2  
**14.4. Packing group:** -  
Hazard label: 2.2  
Special Provisions: A98 A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

**Safety Data Sheet**

according to UK REACH Regulation

**913 Brake Paste MP91300200AB**

Revision date: 22.03.2021

Product code: 1103533

Page 13 of 13

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

**Additional information**Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol Directive (75/324/)**National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,4,7,9,11,14.

**Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Aerosol 3; H229	On basis of test data

**Relevant H and EUH statements (number and full text)**

H229	Pressurised container: May burst if heated.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
EUH208	Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts, Sulfonic acids, petroleum, calcium salts, Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*